

Fitting for top-running glass doors up to 160 kg (352 lbs.), with surface mounted running track or running track flush with the ceiling. Ceiling mounting. Minimal installation height.

Product-Highlights



Aesthetics

Cover caps in different design versions



Productivity

Easy height adjustment via both suspensions on completely installed door

Technical guidelines

Max. Door weight	160 kg (352 lbs.)
Door thickness	8–12.7 mm (5/16" to 1/2")
Max. Door height	4000 mm (13' 1 15/32")
Max. Door width	3000 mm (9' 10 1/8")
Max. Opening width	2950 mm (9' 8 5/32")
Height adjustable	+/- 4 mm (5/32")
Soft close	No
Door material	Glass

System options

Ceiling mounting	Yes
Ceiling mounting recessed	Yes
Top-running	Yes

Application area

Utilization light / semi-public access	Yes
Utilization medium / semi-public access	Yes
Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

Hardware for furniture – Strength and durability of slide fittings for sliding doors and roll fronts according to EN 15706 / 2009

Warranty With the exception of parts subject to wear and tear, Hawa warrants the flawless functioning of the products delivered by it, as well as the durability of all parts, for a period of 2 years commencing from the transfer of risk.

Product Design

Hawa Junior 160 GP consisting of running track (aluminum wall thickness 4.0 mm (5/32")), running gear with friction bearing rollers, stopper, Glass suspension with point fixing, suspension profile with suspension carriage, bottom guide with zero clearance

Optional:

- (...) Guide tracks
- (...) Bottom door stopper, with centering par
- (...) Connector parts to profiles

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing with point fixing