

CERTIFICATE

0960-CPR-SKGIKOB.011089.10.ENG

Issued: 12-12-2023
Valid until: 12-07-2028

Replaces: 0960-CPR-SKGIKOB.011089.09.ENG
Issued: 12-07-2023



Certificate holder

Dulimex BV
Talhoutweg 11
8171 MB Vaassen
T: +31 (0)578 571 124
E: info@dulimex.nl
I: www.dulimex.nl

Certificate of constancy of performance

Declaration of SKG-IKOB (Notified Body 0960)

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

SINGLE-AXIS HINGES

as specified in the attached appendix placed on the market under the name or trade mark of the holder of this certificate and produced by the holder of this certificate or for the holder of this certificate in the manufacturing plant(s) if mentioned above.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1935:2002

and

EN 1935:2002/AC:2003

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 17-07-2018 and will remain valid until the date as mentioned at this certificate as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For SKG-IKOB

A handwritten signature in blue ink, appearing to be 'ir. H.A.J. van Dartel', written over a light blue circular stamp or watermark.

ir. H.A.J. van Dartel
Certification manager

The users of this certificate are advised to verify at www.skgikob.nl if this certificate is still valid and actual.
This certificate consists of 5 pages.



SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

CERTIFICATE

Dulimex BV

Number: 0960-CPR-SKGIKOB.011089.10.ENG

Page 2 of 5

Appendix 1 CERTIFICATE OF CONSTANCY OF PERFORMANCE

Single-axis steel hinges with DX brand

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)																
No bearing: 6710.025.8989-TD No bearing: 6112.025.8989 6712.025.8989 6112.025.8989-TD 6712.025.8989-TD	Dimension; 89x89 mm, thick; 2,4 or 3 mm (round or square) Steel galvanized with burglar resistance pin	<table border="1"> <tr> <td>2</td><td>7</td><td>2</td><td>0</td><td>1</td><td>4</td><td>0</td><td>7</td> </tr> <tr> <td>2</td><td>7</td><td>2</td><td>0</td><td>1</td><td>4</td><td>1</td><td>7</td> </tr> </table>	2	7	2	0	1	4	0	7	2	7	2	0	1	4	1	7	13.0087-04
2	7	2	0	1	4	0	7												
2	7	2	0	1	4	1	7												
Ball bearing: 6210.121.7676 6210.125.7676 6710.125.7676 Ball bearing: 6212.125.7676 6712.125.7676	Dimension; 76x76 mm, thick; 2,4 mm (round or square) Steel galvanized with burglar resistance pin	<table border="1"> <tr> <td>1</td><td>4</td><td>3</td><td>0</td><td>1</td><td>4</td><td>0</td><td>9</td> </tr> <tr> <td>1</td><td>4</td><td>3</td><td>0</td><td>1</td><td>4</td><td>1</td><td>9</td> </tr> </table>	1	4	3	0	1	4	0	9	1	4	3	0	1	4	1	9	16.00299
1	4	3	0	1	4	0	9												
1	4	3	0	1	4	1	9												
Ball bearing: 6210.121.8989 6210.125.8989 6710.125.8989 Ball bearing: 6212.125.8989 6712.125.8989	Dimension; 89x89 mm, thick; 2,4 mm (round or square) Steel galvanized with burglar resistance pin	<table border="1"> <tr> <td>2</td><td>7</td><td>3</td><td>0</td><td>1</td><td>4</td><td>0</td><td>10</td> </tr> <tr> <td>2</td><td>7</td><td>3</td><td>0</td><td>1</td><td>4</td><td>1</td><td>10</td> </tr> </table>	2	7	3	0	1	4	0	10	2	7	3	0	1	4	1	10	15.00314
2	7	3	0	1	4	0	10												
2	7	3	0	1	4	1	10												
Ball bearing: 6710.125.8989-TD Ball bearing: 6712.125.8989-TD	Dimension; 89x89 mm, thick; 3 mm (round or square) Steel galvanized with burglar resistance pin	<table border="1"> <tr> <td>3</td><td>7</td><td>4</td><td>0</td><td>1</td><td>4</td><td>0</td><td>11</td> </tr> <tr> <td>3</td><td>7</td><td>4</td><td>0</td><td>1</td><td>4</td><td>1</td><td>11</td> </tr> </table>	3	7	4	0	1	4	0	11	3	7	4	0	1	4	1	11	17.01272
3	7	4	0	1	4	0	11												
3	7	4	0	1	4	1	11												
Nylon bearing: 6710.154.8989-TD 6710.155.8989-TD Nylon bearing: 6712.154.8989-TD 6712.155.8089-TD / DD 6712.155.8989-TD	Dimension; 80x89 / 89x89 mm, thick; 3 mm (round or square) Steel galvanized (optional varnished) with burglar resistance pin	<table border="1"> <tr> <td>4</td><td>7</td><td>6</td><td>0</td><td>1</td><td>4</td><td>0</td><td>13</td> </tr> <tr> <td>4</td><td>7</td><td>6</td><td>0</td><td>1</td><td>4</td><td>1</td><td>13</td> </tr> </table>	4	7	6	0	1	4	0	13	4	7	6	0	1	4	1	13	17.00328
4	7	6	0	1	4	0	13												
4	7	6	0	1	4	1	13												

CERTIFICATE

Dulimex BV

Number: 0960-CPR-SKGIKOB.011089.10.ENG

Page 3 of 5

Appendix 2

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Single-axis stainless steel hinges with DX brand

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)
No bearing: 6730.033.8989	Dimension; 89x89 mm, thick; 2,4 mm (round or square) Stainless steel	2 7 2 0 1 4 0 7	16.00243
No bearing: 6732.033.8989	with burglar resistance pin	2 7 2 0 1 4 1 7	
Ball pin hinge: 6837.133.8912-5 6837.133.8915-0 6837.233.8912-5 6837.233.8915-0 6937.133.8912-5 6937.133.8915-0 6937.233.8912-5 6937.233.8915-0 6937.134.8912-5 6937.134.8915-0 6937.234.8912-5 6937.234.8915-0	Dimension; 89x125 / 89x150 mm, thick; 3 mm (round or square) Stainless steel (optional black coating)	2 7 2 0 1 4 1 7	18.01071
Ball bearing: 6230.133.7676 6730.133.7676 6230.134.7676 6730.134.7676	Dimension; 76x76 mm, thick; 2,4 mm (round or square) Stainless steel	1 4 3 0 1 4 0 9	16.00846
Ball bearing: 6232.133.7676 6732.133.7676	with burglar resistance pin	1 4 3 0 1 4 1 9	
Ball bearing: 6230.133.8989 6730.133.8989 6230.134.8989 6730.134.8989	Dimension; 89x89 mm, thick; 2,4 mm (round or square) Stainless steel	2 7 3 0 1 4 0 10	16.00243
Ball bearing: 6730.133.8989-DT	Dimension; 89x89 mm, thick; 3 mm (round or square) Stainless steel	3 7 4 0 1 4 0 11	16.00845-1
Ball bearing: 6232.133.8989 6732.133.8989	with burglar resistance pin	3 7 4 0 1 4 1 11	

CERTIFICATE

Dulimex BV

Number: 0960-CPR-SKGIKOB.011089.10.ENG

Page 4 of 5

Appendix 3

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Single-axis stainless steel hinges with DX brand

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)								
Ball pin hinge: 6837.133.8989 6837.233.8989 6937.133.8989 6937.134.8989 6937.233.8989 6937.234.8989	Dimension; 89x89 mm, thick; 3 mm (round or square) Stainless steel	<table border="1"><tr><td>3</td><td>7</td><td>4</td><td>0</td><td>1</td><td>4</td><td>1</td><td>11</td></tr></table>	3	7	4	0	1	4	1	11	18.01070
3	7	4	0	1	4	1	11				

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)								
Nylon bearing: 6730.155.8989-DT	Dimension; 89x89 mm, thick; 3 mm (round or square) Stainless steel	<table border="1"><tr><td>4</td><td>7</td><td>6</td><td>0</td><td>1</td><td>4</td><td>0</td><td>13</td></tr></table>	4	7	6	0	1	4	0	13	19.01061 rev.1
4	7	6	0	1	4	0	13				
Nylon bearing: 6732.155.8989-DT	with burglar resistance pin	<table border="1"><tr><td>4</td><td>7</td><td>6</td><td>0</td><td>1</td><td>4</td><td>1</td><td>13</td></tr></table>	4	7	6	0	1	4	1	13	
4	7	6	0	1	4	1	13				

CERTIFICATE

Dulimex BV

Number: 0960-CPR-SKGIKOB.011089.10.ENG

Page 5 of 5

Appendix 4 CERTIFICATE OF CONSTANCY OF PERFORMANCE

Single-axis Steel hinges with DX brand

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)								
Ball pin hinge: 6872.215.8989-D 6872.215.8989-D 6972.115.8989-D 6972.215.8989-D	Dimension; 89x89 mm, thick; 3 mm (round or square) Steel	<table border="1"><tr><td>2</td><td>7</td><td>3</td><td>0</td><td>1</td><td>4</td><td>1</td><td>10</td></tr></table>	2	7	3	0	1	4	1	10	21.01257-1 Rev.B
2	7	3	0	1	4	1	10				

Article	Specification	Classification according to EN 1935:2002/AC:2003	SKG - ITT (report nr.)								
Ball pin hinge: 6872.115.8912-5 6872.115.8915-0 6872.215.8912-5 6872.215.8912-0 6972.115.8912-5 6972.115.8915-0 6872.215.8912-5 6972.215.8915-0	Dimension; 89x125 mm , 89x150 mm thick; 3 mm (round or square) Steel	<table border="1"><tr><td>2</td><td>7</td><td>2</td><td>0</td><td>1</td><td>4</td><td>1</td><td>7</td></tr></table>	2	7	2	0	1	4	1	7	22.00892
2	7	2	0	1	4	1	7				